

APPENDIX II.Q
Permit No.: UTR000000

Q. Storm Water Discharges Associated With Industrial Activity From Water Transportation Facilities That Have Vehicle Maintenance Shops and/or Equipment Cleaning Operations.

1. Coverage of This Section.

- a. Discharges Covered Under This Section. The requirements listed under this section shall apply to storm water discharges from water transportation facilities that have vehicle (vessel) maintenance shops and/or equipment cleaning operations. The water transportation industry includes facilities engaged in foreign or domestic transport of freight or passengers in deep sea or inland waters; marine cargo handling operations; ferry operations; towing and tugboat services; and marinas (facilities commonly identified by Standard Industrial Classification (SIC) code Major Group 44).
- b. Co-Located Industrial Activity. When an industrial facility, described by the above coverage provisions of this section, has industrial activities being conducted onsite that meet the description(s) of industrial activities in another section(s), that industrial facility shall comply with any and all applicable monitoring and pollution prevention plan requirements of the other section(s) in addition to all applicable requirements in this section. The monitoring and pollution prevention plan terms and conditions of this multi-sector permit are additive for industrial activities being conducted at the same industrial facility. The operator of the facility shall determine which other monitoring and pollution prevention plan section(s) of this permit (if any) are applicable to the facility.

2. Special Conditions.

- a. Prohibition of Non-storm Water Discharges. In addition to the general discharge prohibitions in *Part II.A.*, this section specifically prohibits non-storm water discharges of wastewaters, such as bilge and ballast water, sanitary wastes, pressure wash water, and cooling water originating from vessels. The operators of such discharges must obtain coverage under a separate *UPDES* permit if discharged to waters of the State or through a municipal separate storm sewer system.

3. Storm Water Pollution Prevention Plan Requirements.

- a. Contents of Plan. The plan shall include, at a minimum, the following items:
 - (1) Pollution Prevention Team. Each plan shall identify a specific individual or individuals within the facility organization as members of a storm water Pollution Prevention Team who are responsible for developing the storm water pollution prevention plan and assisting the facility or plant manager in its implementation, maintenance, and revision. The plan shall clearly identify the responsibilities of each team member. The activities and responsibilities of the team shall address all aspects of the facility's storm water pollution prevention plan.

APPENDIX II.Q
Permit No.:UTR000000

- (2) Description of Potential Pollutant Sources. Each plan shall provide a description of potential sources which may reasonably be expected to add significant amounts of pollutants to storm water discharges or which may result in the discharge of pollutants during dry weather from separate storm sewers draining the facility. Each plan shall identify all activities and significant materials which may potentially be significant pollutant sources. Each plan shall include, at a minimum:

(a) Drainage.

- i) A site map indicating an outline of the portions of the drainage area of each storm water outfall that are within the facility boundaries, each existing structural control measure to reduce pollutants in storm water runoff, surface water bodies, locations where significant materials are exposed to precipitation, locations where major spills or leaks identified under paragraph 3.a.(2)(c) (Spills and Leaks) of this section have occurred, and the locations of the following activities where such activities are exposed to precipitation: fueling, engine maintenance and repair, vessel maintenance and repair, pressure washing, painting, sanding, blasting, welding, metal fabrication, loading/unloading areas, locations used for the treatment, storage or disposal of wastes; liquid storage tanks, liquid storage areas (i.e., paint, solvents, resins), and material storage areas (i.e., blasting media, aluminum, steel, scrap iron). In addition, the map must indicate the outfall locations and the types of discharges contained in the drainage areas of the outfalls.
- ii) For each area of the facility that generates storm water discharges associated with industrial activity with a reasonable potential for containing significant amounts of pollutants, a prediction of the direction of flow, and an identification of the types of pollutants which are likely to be present in storm water discharges associated with industrial activity. Factors to consider include the toxicity of chemical; quantity of chemicals used, produced or discharged; the likelihood of contact with storm water; and history of significant leaks or spills of toxic or hazardous pollutants. Flows with a significant potential for causing erosion shall be identified.

- (b) Inventory of Exposed Materials. An inventory of the types of materials handled at the site that potentially may be exposed to precipitation. Such inventory shall include a narrative description of significant materials that have been handled, treated, stored or disposed in a manner to allow exposure to storm water between the time of 3 years prior to the date of the submission of a *Notice of Intent (NOI)* to be covered under this permit and the present; method and location of onsite storage or disposal; materials management practices employed to minimize contact of materials with storm water runoff between the time of 3 years prior to the date of the submission of a *Notice of Intent (NOI)* to be covered under this

APPENDIX II.Q
Permit No.: UTR000000

permit and the present; the location and a description of existing structural and nonstructural control measures to reduce pollutants in storm water runoff; and a description of any treatment the storm water receives.

- (c) Spills and Leaks. A list of significant spills and significant leaks of toxic or hazardous pollutants that occurred at areas that are exposed to precipitation or that otherwise drain to a storm water conveyance at the facility after the date of 3 years prior to the date of the submission of a *Notice of Intent (NOI)* to be covered under this permit. Such list shall be updated as appropriate during the term of the permit.
 - (d) Sampling Data. A summary of existing discharge sampling data describing pollutants in storm water discharges from the facility, including a summary of sampling data collected during the term of this permit.
 - (e) Risk Identification and Summary of Potential Pollutant Sources. A narrative description of the potential pollutant sources from the following activities if applicable: loading and unloading operations; outdoor storage activities; outdoor manufacturing or processing activities (i.e., welding, metal fabricating); significant dust or particulate generating processes (i.e., abrasive blasting, sanding, painting); loading/unloading areas; and onsite waste disposal practices. The description shall specifically list any significant potential source of pollutants at the site and for each potential source, any pollutant or pollutant parameter (e.g., biochemical oxygen demand, etc.) of concern shall be identified.
- (3) Measures and Controls. Each facility covered by this permit shall develop a description of storm water management controls appropriate for the facility, and implement such controls. The appropriateness and priorities of controls in a plan shall reflect identified potential sources of pollutants at the facility. The description of storm water management controls shall address the following minimum components, including a schedule for implementing such controls:
- (a) Good Housekeeping. Good housekeeping requires the maintenance of areas which may contribute pollutants to storm water discharges in a clean, orderly manner. The following areas must be specifically addressed, when applicable at a facility:
 - i) Pressure Washing Area. When pressure washing is used to remove marine growth from vessels, the discharge water must be permitted by a *UPDES* permit. The pollution prevention plan must describe the measures to collect or contain the discharge from the pressure washing area, detail the method for the removal of the visible solids, describe the method of disposal of the collected solids, and identify where the discharge will be released (i.e., the receiving waterbody, storm sewer system, sanitary sewer

APPENDIX II.Q
Permit No.:UTR000000

system).

- ii) Blasting and Painting Areas. The facility must consider containing all blasting and painting activities to prevent abrasives, paint chips, and overspray from reaching the receiving water or the storm sewer system. The plan must describe measures taken at the facility to prevent or minimize the discharge of spent abrasive, paint chips, and paint into the receiving waterbody and storm sewer system. The facility may consider hanging plastic barriers or tarpaulins during blasting or painting operations to contain debris. Where required, a schedule for cleaning storm water conveyances to remove deposits of abrasive blasting debris and paint chips should be addressed within the plan. The plan should include any standard operating practices with regard to blasting and painting activities. Such included items may be the prohibition of performing uncontained blasting and painting over open water or blasting and painting during windy conditions which can render containment ineffective.
- iii) Material Storage Areas. All stored and containerized materials (fuels, paints, solvents, waste oil, antifreeze, batteries) must be stored in a protected, secure location away from drains and plainly labeled. The plan must describe measures that prevent or minimize contamination of the storm water runoff from such storage areas. The facility must specify which materials are stored indoors and consider containment or enclosure for materials that are stored outdoors. Above ground storage tanks, drums, and barrels permanently stored outside must be delineated on the site map with a description of the containment measures in place to prevent leaks and spills. The facility must consider implementing an inventory control plan to prevent excessive purchasing, storage, and handling of potentially hazardous materials. Those facilities where abrasive blasting is performed must specifically include a discussion on the storage and disposal of spent abrasive materials generated at the facility.
- iv) Engine Maintenance and Repair Areas. The plan must describe measures that prevent or minimize contamination of the storm water runoff from all areas used for engine maintenance and repair. The facility may consider performing all maintenance activities indoors, maintaining an organized inventory of materials used in the shop, draining all parts of fluids prior to disposal, prohibiting the practice of hosing down the shop floor, using dry cleanup methods, and/or collecting the storm water runoff from the maintenance area and providing treatment or recycling.
- v) Material Handling Areas. The plan must describe measures that prevent or minimize contamination of the storm water runoff from material handling operations and areas (i.e., fueling, paint and solvent mixing,

APPENDIX II.Q
Permit No.: UTR000000

disposal of process wastewater streams from vessels). The facility may consider covering fueling areas; using spill and overflow protection; mixing paints and solvents in a designated area, preferably indoors or under a shed; and minimizing runoff of storm water to material handling areas or other equivalent measures. Where applicable, the plan must address the replacement or repair of leaking connections, valves, pipes, hoses, and soil chutes carrying wastewater from vessels.

- vi) Drydock Activities. The plan must address the routine maintenance and cleaning of the drydock to minimize the potential for pollutants in the storm water runoff. The plan must describe the procedures for cleaning the accessible areas of the drydock prior to flooding and final cleanup after the vessel is removed and the dock is raised. Cleanup procedures for oil, grease, or fuel spills occurring on the drydock must also be included within the plan. The facility should consider items such as sweeping rather than hosing off debris and spent blasting material from the accessible areas of the drydock prior to flooding and having absorbent materials and oil containment booms readily available to contain and cleanup any spills or other equivalent measures.
- vii) General Yard Area. The plan must include a schedule for routine yard maintenance and cleanup. Scrap metal, wood, plastic, miscellaneous trash, paper, glass, industrial scrap, insulation, welding rods, packaging, etc., must be routinely removed from the general yard area. The facility may consider such measures as providing covered trash receptacles in each yard, on each pier, and on board each vessel being repaired.
- (b) Preventive Maintenance. A preventive maintenance program shall involve timely inspection and maintenance of storm water management devices (e.g., cleaning oil/water separators, sediment traps to ensure that spent abrasives, paint chips, and solids will be intercepted and retained prior to entering the storm drainage system) as well as inspecting and testing facility equipment and systems to uncover conditions that could cause breakdowns or failures resulting in discharges of pollutants to surface waters, and ensuring appropriate maintenance of such equipment and systems.
- (c) Spill Prevention and Response Procedures. Areas where potential spills which can contribute pollutants to storm water discharges can occur, and their accompanying drainage points shall be identified clearly in the storm water pollution prevention plan. Where appropriate, specifying material handling procedures, storage requirements, and use of equipment such as diversion valves in the plan should be considered. Procedures for cleaning up spills shall be identified in the plan and made available to the appropriate personnel. The necessary equipment to implement a clean up should be available to personnel.

APPENDIX II.Q
Permit No.:UTR000000

- (d) Inspections. Qualified facility personnel shall be identified to inspect designated equipment and areas of the facility on a monthly basis. The following areas shall be included in all inspections: pressure washing area; blasting, sanding, and painting areas; material storage areas; engine maintenance and repair areas; material handling areas; drydock area; and general yard area. A set of tracking or follow-up procedures shall be used to ensure that appropriate actions are taken in response to the inspections. Records of inspections shall be maintained.
- (e) Employee Training. Employee training programs shall inform personnel responsible for implementing activities identified in the storm water pollution prevention plan or otherwise responsible for storm water management at all levels of responsibility of the components and goals of the storm water pollution prevention plan. Training should address topics such as spill response, good housekeeping and material management practices. The pollution prevention plan shall identify how often training will take place, but in all cases training must be held at least annually (once per calendar year). Employee training must, at a minimum, address the following areas when applicable to a facility: used oil management; spent solvent management; proper disposal of spent abrasives; proper disposal of vessel wastewaters, spill prevention and control; fueling procedures; general good housekeeping practices; proper painting and blasting procedures; and used battery management. Employees, independent contractors, and customers must be informed about *BMPs* and be required to perform in accordance with these practices. The facility must consider posting instructions, easy to read descriptions or graphic depictions of *BMPs*, spill control/clean-up equipment and emergency phone numbers in the work areas.
- (f) Recordkeeping and Internal Reporting Procedures. A description of incidents (such as spills, or other discharges), along with other information describing the quality and quantity of storm water discharges shall be included in the plan required under this part. Inspections and maintenance activities shall be documented and records of such activities shall be incorporated into the plan.
- (g) Non-storm Water Discharges.
 - i) Certification. The plan shall include a certification that the discharge has been tested or evaluated for the presence of non-storm water discharges. The certification shall include the identification of potential significant sources of non-storm water at the site, a description of the results of any test and/or evaluation for the presence of non-storm water discharges, the evaluation criteria or testing method used, the date of any testing and/or evaluation, and the onsite drainage points that were directly observed during the test. Certifications shall be signed in accordance with *Part VI.G.* of this permit. Such certification may not be feasible if the facility

APPENDIX II.Q
Permit No.: UTR000000

operating the storm water discharge associated with industrial activity does not have access to an outfall, manhole, or other point of access to the ultimate conduit which receives the discharge. In such cases, the source identification section of the storm water pollution prevention plan shall indicate why the certification required by this part was not feasible, along with the identification of potential significant sources of non-storm water at the site. A discharger that is unable to provide the certification required by this paragraph must notify the *Executive Secretary* in accordance with paragraph 3.a.(3)(g)(iii) (below).

- ii) Exceptions. Except for flows from fire fighting activities, sources of non-storm water listed in *Part II.A.2. (Prohibition of Non-storm Water Discharges)* of this permit that are combined with storm water discharges associated with industrial activity must be identified in the plan. The plan shall identify and ensure the implementation of appropriate pollution prevention measures for the non-storm water component(s) of the discharge.
- iii) Failure to Certify. Any facility that is unable to provide the certification required (testing for non-storm water discharges), must notify the *Executive Secretary* by October 1, 1998, or, for facilities which begin to discharge storm water associated with industrial activity after January 1, 1998, 180 days after submitting an *NOI* to be covered by this permit. If the failure to certify is caused by the inability to perform adequate tests or evaluations, such notification shall describe: the procedure of any test conducted for the presence of non-storm water discharges; the results of such test or other relevant observations; potential sources of non-storm water discharges to the storm sewer; and why adequate tests for such storm sewers were not feasible. Non-storm water discharges to waters of the State which are not authorized by a *UPDES* permit are unlawful, and must be terminated.
- (h) Sediment and Erosion Control. The plan shall identify areas which, due to topography, activities, or other factors, have a high potential for significant soil erosion, and identify structural, vegetative, and/or stabilization measures to be used to limit erosion.
- (i) Management of Runoff. The plan shall contain a narrative consideration of the appropriateness of traditional storm water management practices (practices other than those which control the generation or source(s) of pollutants) used to divert, infiltrate, reuse, or otherwise manage storm water runoff in a manner that reduces pollutants in storm water discharges from the site. The plan shall provide that measures that the permittee determines to be reasonable and appropriate shall be implemented and maintained. The potential of various

APPENDIX II.Q
Permit No.:UTR000000

sources at the facility to contribute pollutants to storm water discharges associated with industrial activity [see paragraph 3.a.(2) of this section (Description of Potential Pollutant Sources)] shall be considered when determining reasonable and appropriate measures. Appropriate measures or equivalent measures may include: vegetative swales and practices, reuse of collected storm water (such as for a process or as an irrigation source), inlet controls (such as oil/water separators), snow management activities, infiltration devices, and wet detention/retention devices.

- (4) Comprehensive Site Compliance Evaluation. Qualified personnel shall conduct site compliance evaluations at appropriate intervals specified in the plan, but in no case less than once a year. Such evaluations shall provide:
- (a) Areas contributing to a storm water discharge associated with industrial activity (pressure washing area, blasting and sanding areas, painting areas, material storage areas, engine maintenance and repair areas, material handling areas, and drydock area) shall be visually inspected for evidence of, or the potential for, pollutants entering the drainage system. Measures to reduce pollutant loadings shall be evaluated to determine whether they are adequate and properly implemented in accordance with the terms of the permit or whether additional control measures are needed. Structural storm water management measures, sediment and erosion control measures, and other structural pollution prevention measures identified in the plan shall be observed to ensure that they are operating correctly. A visual inspection of equipment needed to implement the plan, such as spill response equipment, shall be made.
 - (b) Based on the results of the evaluation, the description of potential pollutant sources identified in the plan in accordance with paragraph 3.a.(2) of this section (Description of Potential Pollutant Sources) and pollution prevention measures and controls identified in the plan in accordance with paragraph 3.a.(3) of this section (Measures and Controls) shall be revised as appropriate within 2 weeks of such evaluation and shall provide for implementation of any changes to the plan in a timely manner, but in no case more than 12 weeks after the evaluation.
 - (c) A report summarizing the scope of the evaluation, personnel making the evaluation, the date(s) of the evaluation, major observations relating to the implementation of the storm water pollution prevention plan, and actions taken in accordance with paragraph 3.a.(4)(b) (above) of the permit shall be made and retained as part of the storm water pollution prevention plan for at least 3 years from the date of the inspection. The report shall identify any incidents of noncompliance. Where a report does not identify any incidents of noncompliance, the report shall contain a certification that the facility is in compliance with the storm water pollution prevention plan and this permit. The report shall be signed in accordance with *Part VI.G. (Signatory Requirements)*

of this permit.

- (d) Where compliance evaluation schedules overlap with inspections required under 3.a.(3)(d), the compliance evaluation may be conducted in place of one such inspection.
- 4. Numeric Effluent Limitations. There are no additional numeric effluent limitations beyond those described in *Part IV.B.* of this permit.
- 5. Monitoring and Reporting Requirements.
 - a. Analytical Monitoring Requirements. During the period beginning January 1, 1999, lasting through December 31, 1999, and the period beginning January 1, 2001, lasting through December 31, 2001, permittees with water transportation facilities must monitor their storm water discharges associated with industrial activity at least quarterly (4 times per year) during years 2 and 4 except as provided in paragraphs 5.a.(3) (Sampling Waiver), 5.a.(4) (Representative Discharge), and 5.a.(5) (Alternative Certification). Water transportation facilities are required to monitor their storm water discharges for the pollutants of concern listed in Table Q-1 below. Facilities must report in accordance with 5.b. (Reporting). In addition to the parameters listed in Table Q-1 below, the permittee shall provide the date and duration (in hours) of the storm event(s) sampled; rainfall measurements or estimates (in inches) of the storm event that generated the sampled runoff; the duration between the storm event sampled and the end of the previous measurable (greater than 0.1 inch rainfall) storm event; and an estimate of the total volume (in gallons) of the discharge sampled.

Table Q-1.
Monitoring Requirements

Pollutants of Concern	Monitoring Cut-Off Concentration
Total Recoverable Aluminum	0.75 mg/L
Total Recoverable Iron	1.0 mg/L
Total Recoverable Lead	0.0816 mg/L
Total Recoverable Zinc	0.117 mg/L

- (1) Monitoring Periods. Water transportation facilities shall monitor samples collected during the sampling periods of: January to March, April to June, July to September, and October to December for the years specified in paragraph a. (above).
- (2) Sample Type. A minimum of one grab sample shall be taken. All such samples shall be collected from the discharge resulting from a storm event that is greater than 0.1 inches in magnitude and that occurs at least 72 hours from the previously measurable (greater than 0.1 inch rainfall) storm event. The required 72-hour storm event interval

APPENDIX II.Q
Permit No.:UTR000000

is waived where the preceding measurable storm event did not result in a measurable discharge from the facility. The required 72-hour storm event interval may also be waived where the permittee documents that less than a 72-hour interval is representative for local storm events during the season when sampling is being conducted. The grab sample shall be taken during the first 30 minutes of the discharge. If the collection of a grab sample during the first 30 minutes is impracticable, a grab sample can be taken during the first hour of the discharge, and the discharger shall submit with the monitoring report a description of why a grab sample during the first 30 minutes was impracticable. If storm water discharges associated with industrial activity commingle with process or non-process water, then where practicable permittees must attempt to sample the storm water discharge before it mixes with the non-storm water discharge.

(3) Sampling Waiver.

- (a) Adverse Conditions. When a discharger is unable to collect samples within a specified sampling period due to adverse climatic conditions, the discharger shall collect a substitute sample from a separate qualifying event in the next period and submit the data along with data for the routine sample in that period. Adverse weather conditions that may prohibit the collection of samples include weather conditions that create dangerous conditions for personnel (such as local flooding, high winds, hurricane, tornadoes, electrical storms, etc.) or otherwise make the collection of a sample impracticable (drought, extended frozen conditions, etc.).
- (b) Low Concentration Waiver. When the average concentration for a pollutant calculated from all monitoring data collected from an outfall during the monitoring period January 1, 1999, lasting through December 31, 1999, is less than the corresponding value for that pollutant listed in Table Q-1 under the column Monitoring Cut-Off Concentration, a facility may waive monitoring and reporting requirements in the monitoring period beginning January 1, 2001, lasting through December 31, 2001. The facility must submit to the *Executive Secretary*, in lieu of the monitoring data, a certification that there has not been a significant change in industrial activity or the pollution prevention measures in area of the facility which drains to the outfall for which sampling was waived.
- (c) Inactive and Unstaffed Site. When a discharger is unable to conduct quarterly chemical storm water sampling at an inactive and unstaffed site, the operator of the facility may exercise a waiver of the monitoring requirements as long as the facility remains inactive and unstaffed. The facility must submit to the *Executive Secretary*, in lieu of monitoring data, a certification statement on the *Storm Water Discharge Monitoring Report (SWDMR)* stating that the site is inactive and unstaffed so that collecting a sample during a qualifying event is not possible.

APPENDIX II.Q
Permit No.: UTR000000

- (4) Representative Discharge. When a facility has two or more outfalls that, based on a consideration of industrial activity, significant materials, and management practices and activities within the area drained by the outfall, the permittee reasonably believes discharge substantially identical effluents, the permittee may test the effluent of one of such outfalls and report that the quantitative data also applies to the substantially identical outfall(s) provided that the permittee includes in the storm water pollution prevention plan a description of the location of the outfalls and explains in detail why the outfalls are expected to discharge substantially identical effluents. In addition, for each outfall that the permittee believes is representative, an estimate of the size of the drainage area (in square feet) and an estimate of the runoff coefficient of the drainage area [e.g., low (under 40 percent), medium (40 to 65 percent), or high (above 65 percent)] shall be provided in the plan. The permittee shall include the description of the location of the outfalls, explanation of why outfalls are expected to discharge substantially identical effluents, and estimate of the size of the drainage area and runoff coefficient with the *SWDMR*.
- (5) Alternative Certification. A discharger is not subject to the monitoring requirements of this section provided the discharger makes a certification for a given outfall or on a pollutant-by-pollutant basis in lieu of monitoring reports required under paragraph *b.* below, under penalty of law, signed in accordance with *Part VI.G.* (Signatory Requirements), that material handling equipment or activities, raw materials, intermediate products, final products, waste materials, by-products, industrial machinery or operations, or significant materials from past industrial activity that are located in areas of the facility within the drainage area of the outfall are not presently exposed to storm water and are not expected to be exposed to storm water for the certification period. Such certification must be retained in the storm water pollution prevention plan, and submitted to *DWQ* in accordance with *Part V.B.* of this permit. In the case of certifying that a pollutant is not present, the permittee must submit the certification along with the monitoring reports required under paragraph *b.* below. If the permittee cannot certify for an entire period, they must submit the date exposure was eliminated and any monitoring required up until that date. This certification option is not applicable to compliance monitoring requirements associated with effluent limitations.
- b. Reporting. Permittees with water transportation facilities shall submit monitoring results for each outfall associated with industrial activity [or a certification in accordance with paragraphs (3), (4), or (5) above] obtained during the reporting period beginning January 1, 1999, lasting through December 31, 1999, on *SWDMR* form(s) postmarked no later than the 31st day of the following March, 2000. Monitoring results [or a certification in accordance with paragraphs (3), (4), or (5) above] obtained during the period beginning January 1, 2001, lasting through December 31, 2001, shall be submitted on *SWDMR* form(s) postmarked no later than the 31st day of the following March. For each outfall, one signed *SWDMR* form must be submitted to the *Executive Secretary* per storm event sampled. Signed copies of *SWDMRs*, or said certifications, shall be submitted to the *Executive Secretary* at the address

APPENDIX II.Q
Permit No.:UTR000000

listed in *Part V.B.* of the permit.

- (1) Additional Notification. In addition to filing copies of *SWDMRs* in accordance with paragraph *b.* (above), water transportation facilities with at least one storm water discharge associated with industrial activity through a large or medium municipal separate storm sewer system (systems serving a population of 100,000 or more) must submit signed copies of *SWDMRs* to the operator of the municipal separate storm sewer system in accordance with the dates provided in paragraph *b.* (above).
- c. Quarterly Visual Examination of Storm Water Quality. Facilities shall perform and document a visual examination of a storm water discharge associated with industrial activity from each outfall, except discharges exempted below. The examination must be made at least once in each designated period [described in paragraph (1) below] during daylight hours unless there is insufficient rainfall or snow melt to produce a runoff event.
 - (1) Visual Monitoring Period. Examinations shall be conducted in each of the following periods for the purposes of visually inspecting storm water quality associated with storm water runoff or snowmelt: January through March; April through June; July through September; and October through December.
 - (2) Sample and Data Collection. Examinations shall be made of samples collected within the first 30 minutes (or as soon thereafter as practical, but not to exceed 1 hour) of when the runoff or snowmelt begins discharging. The examinations shall document observations of color, odor, clarity, floating solids, settled solids, suspended solids, foam, oil sheen, and other obvious indicators of storm water pollution. The examination must be conducted in a well lit area. No analytical tests are required to be performed on the samples. All such samples shall be collected from the discharge resulting from a storm event that is greater than 0.1 inches in magnitude and that occurs at least 72 hours from the previously measurable (greater than 0.1 inch rainfall) storm event. Where practicable, the same individual should carry out the collection and examination of discharges for entire permit term.
 - (3) Visual Storm Water Discharge Examination Report. Visual examination reports must be maintained onsite in the pollution prevention plan. The report shall include the examination date and time, examination personnel, the nature of the discharge (i.e., runoff or snow melt), visual quality of the storm water discharge (including observations of color, odor, clarity, floating solids, settled solids, suspended solids, foam, oil sheen, and other obvious indicators of storm water pollution), and probable sources of any observed storm water contamination.
 - (4) Representative Discharge. When a facility has two or more outfalls that, based on a consideration of industrial activity, significant materials, and management practices and activities within the area drained by the outfall, the permittee reasonably believes discharge substantially identical effluents, the permittee may collect a sample of

APPENDIX II.Q
Permit No.: UTR000000

effluent of one of such outfalls and report that the examination data also applies to the substantially identical outfall(s) provided that the permittee includes in the storm water pollution prevention plan a description of the location of the outfalls and explains in detail why the outfalls are expected to discharge substantially identical effluents. In addition, for each outfall that the permittee believes is representative, an estimate of the size of the drainage area (in square feet) and an estimate of the runoff coefficient of the drainage area [e.g., low (under 40 percent), medium (40 to 65 percent), or high (above 65 percent)] shall be provided in the plan.

- (5) Adverse Conditions. When a discharger is unable to collect samples over the course of the visual examination period as a result of adverse climatic conditions, the discharger must document the reason for not performing the visual examination and retain this documentation onsite with the records of the visual examination. Adverse weather conditions which may prohibit the collection of samples include weather conditions that create dangerous conditions for personnel (such as local flooding, high winds, hurricane, tornadoes, electrical storms, etc.) or otherwise make the collection of a sample impracticable (drought, extended frozen conditions, etc.).
- (6) Inactive and Unstaffed Site. When a discharger is unable to conduct visual storm water examinations at an inactive and unstaffed site, the operator of the facility may exercise a waiver of the monitoring requirement as long as the facility remains inactive and unstaffed. The facility must maintain a certification with the pollution prevention plan stating that the site is inactive and unstaffed so that performing visual examinations during a qualifying event is not feasible.